

IN THE CLAIMS

1. (currently amended) An objective employed for use in inspecting a specimen, comprising:

a focusing lens group comprising at least one focusing lens configured to receive said light energy and form focused light energy;

a plurality of field lenses oriented to receive focused light energy from said focusing lens group and provide intermediate light energy;

a Mangin mirror arrangement positioned to receive the intermediate light energy from the plurality of field lenses through a back side of the Mangin mirror arrangement and form controlled light energy transmitted from a front side of the Mangin mirror arrangement, said Mangin mirror arrangement comprising at least three axially distributed elements comprising two elements having reflective surfaces; and

an immersion liquid between the Mangin mirror arrangement and the specimen, wherein the third element of the Mangin mirror arrangement is in contact with the immersion liquid;

~~wherein said objective is configured to be usable with light energy having a wavelength in the range of approximately 190 to 1000 nanometers.~~

2. (original) The objective of claim 1, wherein said objective provides a relative bandwidth in excess of 0.5 in the presence of said light energy.

3. (original) The objective of claim 1, said Mangin mirror arrangement comprising:

a first lens/mirror element having substantially curved concave surfaces and a second surface reflection; and

a second lens/mirror element having minimally curved surfaces and a second surface reflection.

4. (currently amended) The objective of claim 3, wherein ~~said Mangin mirror arrangement further comprises a third lens element having one surface in contact with the immersion liquid~~ said objective is configured to be usable with light energy having a wavelength in the range of approximately 190 to 1000 nanometers

5. (original) The objective of claim 1, configured to have a numerical aperture in excess of approximately 0.9.

6. (original) The objective of claim 1, configured to have a numerical aperture in excess of approximately 1.1.

7. (canceled)

8. (previously presented) The objective of claim 1, wherein each lens in the focusing lens group and the plurality of field lenses each has a diameter of less than approximately 25 millimeters.

9. (original) The objective of claim 1, wherein all lenses are constructed of a single glass material.

10. (canceled)

11. (currently amended) The objective of claim ~~[[1]]~~ 9, wherein the single glass material is fused silica.

12. (canceled)

13. (previously presented) The objective of claim 2, said objective providing bandwidth less than approximately 0.9 with a center wavelength of 633 nm.

14. (previously presented) The objective of claim 2, wherein bandwidth is less than approximately 0.07 with a center wavelength of 196nm.

15. (canceled)

16. (canceled)

17. (original) The objective of claim 1, wherein said objective is employed with a microscope having a flange, wherein the flange may be located approximately 45 millimeters from the specimen.

18. (original) The objective of claim 1, wherein said objective is employed with a microscope having a flange, wherein the flange may be located approximately 100 millimeters from the specimen.

19. (original) The objective of claim 1, wherein said focusing lens and field lens forms an intermediate image between said field lens and said Mangin mirror arrangement.

20-63. (canceled)

64. (original) The objective of claim 1, where the immersion liquid has a refractive index greater than pure water.

65. (canceled)

66. (canceled)

67. (currently amended) An objective, comprising:

a focusing lens group comprising at least one focusing lens configured to receive light energy and form focused light energy;

a field lens oriented to receive focused light energy from said focusing lens group and provide intermediate light energy;

a Mangin mirror arrangement positioned to receive the intermediate light energy from the field lens through a backside of said Mangin mirror arrangement and form controlled light energy using a front side of said Mangin mirror arrangement, wherein the Mangin mirror arrangement comprises first and second lens/mirror elements each having curved concave surfaces and second surface reflection and a third lens element; and

an immersion liquid between the Mangin mirror arrangement and a specimen, wherein the third lens element is in contact with the immersion liquid;

~~wherein said Mangin mirror arrangement is configured to impart the controlled light energy to the specimen with a numerical aperture in excess of 0.9 and a field size of greater than or equal to approximately 0.10 mm.~~

68. (previously presented) The objective of claim 67, wherein said objective provides a relative bandwidth in excess of 0.5 in the presence of said light energy.

69. (currently amended) The objective of claim 67, said Mangin mirror arrangement comprising:

[[a]] the first lens/mirror element having substantially curved concave surfaces and a second surface reflection; and

[[a]] the second lens/mirror element having minimally curved surfaces and a second surface reflection.

70. (currently amended) The objective of claim 69, wherein said ~~Mangin mirror arrangement further comprises a third lens element~~ has having one relatively flat surface in contact with the immersion liquid.

71. (previously presented) The objective of claim 67, wherein said objective is configured to be used with light energy having a wavelength in the range of approximately 190 to 1000 nanometers.

72. (previously presented) The objective of claim 67, configured to have a numerical aperture in excess of approximately 1.1.

73. (previously presented) The objective of claim 67, wherein each lens in the focusing lens group and the field lens each has a diameter of less than approximately 25 millimeters.

74. (previously presented) The objective of claim 67, wherein all lenses are constructed of a single glass material.

75. (currently amended) An objective employed for use in inspecting a specimen, comprising:

a focusing lens group configured to receive light energy and comprising at least one focusing lens;

at least one field lens oriented to receive focused light energy from said focusing lens group and provide intermediate light energy;

a Mangin mirror arrangement positioned to receive the intermediate light energy from the field lens through a back side of the Mangin mirror arrangement and form controlled light energy using a front side of the Mangin mirror arrangement; and

an immersion liquid located between said Mangin mirror arrangement and said specimen;

wherein the Mangin mirror arrangement comprises first and second lens/mirror elements each having curved concave surfaces and second surface reflection and a third lens element, wherein the third lens element is in contact with the immersion liquid said Mangin mirror arrangement imparting the controlled light energy to the specimen with a numerical aperture in excess of 0.9 and a field size of greater than or equal to approximately 0.10 mm.

76. (previously presented) The objective of claim 75, wherein said objective provides a relative bandwidth in excess of 0.5 in the presence of said light energy, said light energy having a wavelength in the range of approximately 157 nanometers through the infrared light range.

77. (currently amended) The objective of claim 75, said Mangin mirror arrangement comprising:

[[a]] first lens/mirror element having substantially curved concave surfaces and [[a]] second surface reflection; and

[[a]] second lens/mirror element having minimally curved surfaces and [[a]] second surface reflection.

78. (currently amended) The objective of claim 75, wherein said objective is configured to be usable with light energy having a wavelength in the range of approximately 190 to 1000 nanometers ~~said Mangin mirror arrangement comprising:~~

~~a first lens/mirror element having substantially curved concave surfaces and a second surface reflection; and~~

~~a second lens/mirror element having minimally curved surfaces and a second surface reflection; and~~

~~a third lens element having one surface in contact with the immersion liquid.~~

79. (previously presented) The objective of claim 75, wherein each lens in the objective has a diameter of less than approximately 25 millimeters.

80. (previously presented) The objective of claim 75 where the numerical aperture is greater than approximately 0.9.

81. (previously presented) The objective of claim 75, where the numerical aperture is greater than approximately 1.1.

82. (previously presented) The objective of claim 75, wherein all lenses in the objective are constructed of a single glass material.

83. (previously presented) The objective of claim 82, wherein the single glass material is fused silica.

84. (previously presented) The objective of claim 75, wherein corrected bandwidth for the objective is less than approximately 0.9 with a center wavelength of approximately 633 nm.

85. (previously presented) The objective of claim 75, wherein corrected bandwidth is less than approximately 0.07 with a center wavelength of approximately 196 nm.

86. (previously presented) The objective of claim 75, wherein said objective may be located in a flange within a microscope, said flange positioned no more than approximately 45 millimeters from the specimen during normal operation.

87. (previously presented) The objective of claim 75, wherein said objective may be located in a flange within a microscope, said flange positioned no more than approximately 100 millimeters from the specimen during normal operation.

88. (previously presented) The objective of claim 75, wherein the immersion liquid is primarily water.

89. (previously presented) The objective of claim 75, wherein the immersion liquid is primarily oil.

90. (previously presented) The objective of claim 75, wherein the immersion liquid is primarily silicone gel.

91. (previously presented) The objective of claim 75, wherein the objective is optimized to produce relatively minimal spherical aberration, axial color, and chromatic variation of aberrations.

92. (previously presented) The objective of claim 75, said objective having a numerical aperture of greater than approximately 1.0 at the specimen.

93. (previously presented) The objective of claim 75, wherein each lens in the objective has a diameter of less than approximately 35 millimeters.

94. (previously presented) The objective of claim 75, said objective having an ability to be employed with a microscope having a flange, wherein the flange may be located less than no more than approximately 45 millimeters from the specimen during normal operation.

95. (previously presented) The objective of claim 75, said objective employing no more than two glass materials.

96. (previously presented) The objective of claim 95, wherein the no more than two glass materials comprise fused silica and calcium fluoride.

97. (previously presented) The objective of claim 75, wherein the immersion liquid comprises one from a group comprising water, oil, and silicone gel.

98. (previously presented) The objective of claim 75, where the immersion liquid has a refractive index greater than pure water.